

EW132-137

EW132, HELIAX® Standard Elliptical Waveguide, 13.75–14.8 GHz, black PE jacket



OBSOLETE

This product was discontinued on: January 2, 2024

Product Classification

Product Type	Standard elliptical waveguide
Product Brand	HELIAX®
Product Series	Standard

General Specifications

Jacket Color	Black
Performance Note	Values typical, unless otherwise stated

Dimensions

Diameter Over Jacket (E Plane)	24.4 mm 0.961 in
Diameter Over Jacket (H Plane)	15.5 mm 0.61 in
Cable Volume	167 L/km 1.798 ft³/kft

Electrical Specifications

eTE11 Mode Cutoff	9.22 GHz
Group Delay at Frequency	131 ns/100 ft @ 14.700 GHz 428 ns/100 m @ 14.700 GHz
Operating Frequency Band	13.75 – 14.8 GHz

VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
13.75–14.8 GHz	1.15	23.13

EW132-137

Attenuation

Frequency (GHz)	Attenuation (dB/100 m)	Attenuation (dB/100 ft)	Average Power (kW)	Group Velocity %
13.75	16.576	5.052	0.814	74.2
13.95	16.388	4.995	0.824	75
14.15	16.215	4.942	0.833	75.9
14.35	16.056	4.894	0.841	76.6
14.55	15.909	4.849	0.849	77.4
14.75	15.773	4.808	0.856	78.1

Material Specifications

Conductor Material	Corrugated copper
Jacket Material	PE

Mechanical Specifications

Minimum Bend Radius, Multiple Bends (E Plane)	130 mm 5.118 in
Minimum Bend Radius, Multiple Bends (H Plane)	360 mm 14.173 in
Minimum Bend Radius, Single Bend (E Plane)	130 mm 5.118 in
Minimum Bend Radius, Single Bend (H Plane)	360 mm 14.173 in
Maximum Twist	6.562 °/m 2 °/ft

Environmental Specifications

Installation temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Operating Temperature	-55 °C to +85 °C (-67 °F to +185 °F)
Storage Temperature	-70 °C to +85 °C (-94 °F to +185 °F)
Attenuation, Ambient Temperature	75 °F 23.889 °C
Average Power, Ambient Temperature	104 °F 40 °C
Average Power, Temperature Rise	42 °C 107.6 °F

Packaging and Weights

Cable weight	0.33 kg/m 0.222 lb/ft
---------------------	-------------------------

Regulatory Compliance/Certifications

Agency	Classification
--------	----------------

EW132-137

CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

