

Fiber Optic Cable, 12-fiber, 1 x 12, OM2 plus, ULSZH, orange

OBSOLETE

This product was discontinued on: June 13, 2018

Product Classification

| | |
|------------------------------|-------------------------------------|
| Regional Availability | Asia Australia/New Zealand EMEA |
| Portfolio | CommScope® |
| Product Type | Fiber indoor/outdoor cable |

General Specifications

| | |
|-------------------------------------|--------------|
| Cable Type | Tight buffer |
| Fibers per Subunit, quantity | 12 |
| Jacket Color | Orange |
| Total Fiber Count | 12 |

Dimensions

| | |
|-----------------------------|-----------------------|
| Cable Length | 4000 m 13,123.36 ft |
| Diameter Over Jacket | 7.5 mm 0.295 in |

Mechanical Specifications

| | |
|--|----------------------|
| Minimum Bend Radius, loaded | 115 mm 4.528 in |
| Minimum Bend Radius, unloaded | 75 mm 2.953 in |
| Tensile Load, long term, maximum | 600 N 134.885 lbf |
| Tensile Load, short term, maximum | 1000 N 224.809 lbf |

Optical Specifications

| | |
|-------------------|------|
| Fiber Type | OM2+ |
|-------------------|------|

Optical Specifications, Wavelength Specific

| | |
|-----------------------------|---------------------------------|
| Attenuation, maximum | 0.70 dB/km @ 1,300 nm |
| Standards Compliance | IEC 60794-1 TIA-492AAAB (OM2) |

4-599148-6

Environmental Specifications

| | |
|---|--|
| Installation temperature | -5 °C to +50 °C (+23 °F to +122 °F) |
| Operating Temperature | -20 °C to +70 °C (-4 °F to +158 °F) |
| Storage Temperature | -20 °C to +70 °C (-4 °F to +158 °F) |
| EN50575 CPR Cable EuroClass Fire Performance | Dca |
| EN50575 CPR Cable EuroClass Smoke Rating | s2 |
| EN50575 CPR Cable EuroClass Droplets Rating | d1 |
| EN50575 CPR Cable EuroClass Acidity Rating | a1 |
| Environmental Space | Universal Low Smoke Zero Halogen (ULSZH) |

Packaging and Weights

| | |
|---------------------|-------------------------|
| Cable weight | 56 kg/km 37.63 lb/kft |
|---------------------|-------------------------|

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|--|
| CENELEC | EN 50575 compliant, Declaration of Performance (DoP) available |
| CHINA-ROHS | Below maximum concentration value |
| REACH-SVHC | Compliant as per SVHC revision on www.commscope.com/ProductCompliance |
| ROHS | Compliant |



* Footnotes

Operating Temperature Specification applicable to non-terminated bulk fiber cable