

#### FDH 3000 Plug-and-Play Splitter Module, 2x8, SC/APC

- Rugged packaging is built for high performance, while the Plug-and-Play design reduces installation time
- Bend-optimized fiber and ruggedized extreme temperature cabling
- Easy to insert and remove without affecting adjacent splitters
- Reversible dust cap makes test and turn-up easy
- \*Product complies with the Build America, Buy America Act (BABAA) requirements of the Infrastructure Investment and Jobs Act of 2021 (Pub. L. 117- 58, §§ 70901-70953), or is the subject of a waiver approved by the Secretary of Commerce or designee. Compliance requirements and waiver applicability vary based on government funding program. Check the laws and regulations for your specific program.

#### Product Classification

Regional Availability	Latin America   North America
Portfolio	CommScope®
Product Type	Splitter module
Product Series	FDH 3000   Mini FDH 3000
Government Funding	Build America Buy America (BABA) compliant*
General Specifications	
Device Type	Plug-and-play module
Functionality	Splitting
Access	Front   Rear
Application	For use in FDH 3000 cabinets
Circuits, quantity	2
Distribution Type	2 x 8 splitter
Interface, front	SC/APC
Interface, Input	SC/APC
Interface, Output	SC/APC
Interface, rear	SC/APC
Module Color	Putty white
Split Ratio	Symmetrical
Splitter, quantity	2

Page 1 of 2

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: April 11, 2024



# FPS-MPP1KJJ

#### Dimensions

Height	88.9 mm   3.5 in
Width	12.7 mm   0.5 in
Depth	139.7 mm   5.5 in
Furcation Tube Diameter	2 mm   0.079 in

#### **Optical Specifications**

Directivity, minimum	60 dB
Polarization Dependent Loss, maximum	0.2 dB
Uniformity, maximum	1 dB
Wavelength Range	1260-1635 nm
Insertion Loss, Splitter, maximum	10.7 dB
Insertion Loss, Splitter, typical	9.8 dB
Return Loss, Splitter, minimum	55 dB

#### **Environmental Specifications**

Operating Temperature	-55 °C to +85 °C (-67 °F to +185 °F)	
Flammability Rating	UL 94 V-0	
Qualification Standards	Telcordia GR-1209-CORE   Telcordia GR-1221-CORE   Telcordia GR-326-CORE	

### Packaging and Weights

Included	Reversible dust cap
Packaging quantity	1
Packaging Type	Bag   Carton

## Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted



Page 2 of 2

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: April 11, 2024

