760244973 | CHD-SP-12LC-LS-B-ULL



CHD ULL Multimode OM4 Splice Cassette, 12LC, with dust plugs and pigtails

Product Classification

Regional Availability Asia | Australia/New Zealand | EMEA | Latin America | North America

Portfolio CommScope®

Product Type Fiber cassette with pigtails

Product Brand SYSTIMAX ULL

Product Series CHD

General Specifications

Color, front Aqua
Interface, front LC/UPC

Interface, rear Stranded pigtail

Polarity Method B Enhanced

Shuttered No Total Fibers, quantity 12

Dimensions

 Height
 12.446 mm | 0.49 in

 Width
 83.82 mm | 3.3 in

 Depth
 184.658 mm | 7.27 in

Optical Specifications

Fiber Mode Multimode

Fiber Type OM4, LazrSPEED® 550

Insertion Loss, maximum 0.15 dB

Environmental Specifications



760244973 | CHD-SP-12LC-LS-B-ULL

Qualification Standards IEC 61753-1 | TIA-568.3-D

Safety Standard CE | CSA | UL

Packaging and Weights

Included Single Fusion Splice Protection Sleeves

Packaging quantity 1

Weight, net 0.095 kg | 0.21 lb

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant



Included Products

FST-ACC005 - Fiber Optic Protective Splice Sleeve, 1

package



FST-ACC005



Fiber Optic Protective Splice Sleeve, 1 package

Product Classification

Regional Availability North America

Product Type Fiber protection sleeve

General Specifications

Splicing Type Heat shrink, single fiber fusion

Environmental Specifications

Storage Temperature $-40 \,^{\circ}\text{C}$ to $+85 \,^{\circ}\text{C}$ (-40 $^{\circ}\text{F}$ to $+185 \,^{\circ}\text{F}$)

Packaging and Weights

Packaging quantity

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant



