CMAX-DMH60-43-V53



Cell-Max[™] Low PIM Directional High Capacity Venue MIMO Antenna, 1690–2700 MHz, 60°, 4x4 MIMO, 4.3-10

OBSOLETE

This product was discontinued on: July 31, 2021 Replaced By:

CMAX-DM60-43-UWI53 Cell-Max™ Low PIM Directional High Capacity Venue MIMO Antenna, 617-960 MHz 1695-2700 MHz,

3300-4000MHz, and 4800-6000MHz 60-Deg, 4.3-10, (2 PORTS 617-960 and 1695-2700MHz, 2 PORTS

3300-4000 and 4800-6000MHz)

Product Classification

Product Type Over-the-head stadium antenna

Product Brand Cell-Max™

General Specifications

Application Indoor/Outdoor

Antenna Type Directional
Antenna Array Characteristic MIMO 4x4

Polarization $\pm 45^{\circ}$ ColorWhiteNumber of Ports4

Pigtail Cable 670-141SXE, plenum rated

Radome Material ABS, UV resistant

RF Connector Interface 4.3-10 Male

Dimensions

 Height
 100 mm | 3.937 in

 Width
 180 mm | 7.087 in



CMAX-DMH60-43-V53

 Length
 310 mm | 12.205 in

 Pigtail Length
 910 mm | 35.827 in

Electrical Specifications

Impedance50 ohmLightning Protectiondc Ground

Electrical Specifications

Frequency Band, MHz	1690-2170	2200-2600	2600-2700
Gain, dBi	7.7	8.3	8.3
Beamwidth, Horizontal, degrees	68	62	62
Beamwidth, Vertical, degrees	66	62	62
Front-to-Back Ratio at 180°, dB	30	30	30
CPR at Boresight, dB	15	15	15
Isolation, Cross Polarization, dB	24	24	24
VSWR Return loss, dB	1.5 14.0	1.5 14.0	1.7 11.7
PIM, 3rd Order, 2 x 20 W, dBc	-153	-153	-153
Input Power per Port, maximum, watts	50	50	50

Environmental Specifications

Operating Temperature $-40 \,^{\circ}\text{C} \text{ to } +60 \,^{\circ}\text{C} \, (-40 \,^{\circ}\text{F to } +140 \,^{\circ}\text{F})$

Relative Humidity Up to 100%

Ingress Protection Test Method IEC 60529:2001, IP65

Vibration Test Method ASTM D4169 | IEC 60068-2-6

Packaging and Weights

 Height, packed
 230 mm | 9.055 in

 Width, packed
 400 mm | 15.748 in

 Length, packed
 420 mm | 16.535 in

 Included
 Mounting bracket

Packaging quantity 1

 Weight, gross
 4.8 kg | 10.582 lb

 Weight, net
 1.6 kg | 3.527 lb



CMAX-DMH60-43-V53

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant

