### SC/APC Connector, Singlemode, Green

#### **OBSOLETE**

#### **Product Classification**

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

Portfolio CommScope®
Product Type Fiber connector

General Specifications

Color, bootGreenColor, housingGreenInterfaceSC/APC

**Dimensions** 

**Length** 52 mm | 2.047 in

Material Specifications

Ferrule Material Zirconia

Mechanical Specifications

Cable Retention Strength, maximum 1.00 lb @ 0 °

Optical Specifications

**Fiber Mode** Singlemode

**Insertion Loss Change, mating** 0.2 dB

Optical Components Standard ANSI/TIA-568. 3-D | IEC 61753-1

Insertion Loss Change, temperature0.3 dBInsertion Loss, typical0.3 dBReturn Loss, minimum55 dB

### Regulatory Compliance/Certifications

Agency Classification

**COMMSCOPE®** 

# 460125859

CHINA-ROHS Above maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

ROHS Compliant/Exempted UK-ROHS Compliant/Exempted



## \* Footnotes

**Insertion Loss Change, mating**TIA-568: Maximum insertion loss change after 500 matings

**Insertion Loss Change, temperature** Maximum insertion loss change from -10 °C to +60 °C (+14 °F to +140 °F)

