## 567271-000 | OCC1D-A-484-NNSEN-2T



OCC1D compact DWDM, 4 channels + upgrade port, single demux, 1538.98 nm starting wavelength, 0.9 mm cable, ruggedized housing

#### **OBSOLETE**

This product was discontinued on: July 25, 2023

### Product Classification

Regional Availability Asia | Australia/New Zealand | EMEA | Latin America | North America

Product Type DWDM component

Product Series OCC1D

## General Specifications

**Device Type** Component, rectangular

**Functionality** Demultiplexing

**Technology Type** Thin film filter (TFF)

**Application** For use in FOSC closures

Circuits, quantity

**Distribution Type** 4-channel DWDM

Interface, InputStub tailInterface, OutputStub tail

Multiplexers, quantity 1

Port Type, optional Upgrade port

### **Dimensions**

 Height
 9.14 mm | 0.36 in

 Width
 60.96 mm | 2.4 in

 Depth
 3.97 mm | 0.156 in



# 567271-000 | OCC1D-A-484-NNSEN-2T

Pigtail Length, Input1 m | 3.281 ftPigtail Length, Output1 m | 3.281 ftPigtail Diameter0.9 mm | 0.035 in

### **Optical Specifications**

Channel Spacing 100 GHz
Starting Wavelength 1,538.98 nm

## Packaging and Weights

Packaging quantity

## Regulatory Compliance/Certifications

### Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant

