

Twin Diplexer, DCS 1800/UMTS 2100, AISG compatible, (DC Smart Bypass), with 4.3-10 connectors.

- Industry leading PIM performance
- Minimal Insertion Loss
- New 4.3-10 connectors for improved PIM performance and size reduction

Product Classification

Product Type	Diplexer
General Specifications	
Color	Gray
Common Port Label	PORT 3 COMMON
Modularity	2-Twin
Mounting	Pole Wall
Mounting Pipe Hardware	Band clamps (2)
RF Connector Interface	4.3-10 Female
RF Connector Interface Body Style	Long neck
Dimensions	
Height	149 mm 5.866 in
Width	145 mm 5.709 in
Depth	143 mm 5.63 in
RF Connector Length	25 mm 0.984 in
Mounting Pipe Diameter Range	40-160 mm

Outline Drawing

Page 1 of 4

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: January 19, 2024





Electrical Specifications

Impedance	50 ohm		
License Band, Band Pass	DCS 1800	I	IMT 2100

Electrical Specifications, dc Power/Alarm

dc/AISG Pass-through Method	Auto sensing
dc/AISG Pass-through, combiner	Autosensing
dc/AISG Pass-through, demultiplexer	Autosensing
Lightning Surge Current	3 kA
Lightning Surge Current Waveform	10/350 waveform

Electrical Specifications

Sub-module	1 2	1 2
Branch	1	2
Port Designation	PORT 2 1710-1880	PORT 1 1920-2170
License Band	DCS 1800, Band Pass	IMT 2100, Band Pass
Electrical Specifications, Band Pass		
Frequency Range, MHz	1710-1880	1920-2170

Page 2 of 4

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: January 19, 2024

COMMSCOPE°

Insertion Loss, typical, dB	0.25	0.35
Return Loss, typical, dB	20	20
Isolation, minimum, dB	50	50
Input Power, RMS, maximum, W	250	250
Input Power, PEP, maximum, W	2500	2500
3rd Order PIM, typical, dBc	-161	
3rd Order PIM Test Method	2 x 20 W CW tones	
7th Order PIM, typical, dBc		-168
7th Order PIM Test Method		2 x 20 W CW tones

Block Diagram



Environmental Specifications

Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Corrosion Test Method	IEC 60068-2-11, 30 days
Ingress Protection Test Method	IEC 60529:2001, IP67

Packaging and Weights

Included	Mounting hardware	
Volume	2.5 L	
Weight, net	3.9 kg 8.598 lb	

Regulatory Compliance/Certifications

Classification

Page 3 of 4

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: January 19, 2024



ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

Page 4 of 4

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: January 19, 2024

