

# T-10-UW-43-M

---



Termination Load, 0–6000 MHz, Not for PIM-rated applications

## Product Classification

|                              |   |
|------------------------------|---|
| <b>Regional Availability</b> | Asia   Australia/New Zealand   EMEA   Latin America   North America |
| <b>Product Type</b>          | Termination Load  |

## General Specifications

|                              |                  |
|------------------------------|------------------|
| <b>Device Type</b>           | Termination Load |
| <b>Application</b>           | Indoor/Outdoor   |
| <b>Color</b>                 | Black            |
| <b>Inner Contact Plating</b> | Silver           |
| <b>Interface</b>             | 4.3-10 Male      |
| <b>Outer Contact Plating</b> | Trimetal         |

## Dimensions

|                          |                  |
|--------------------------|------------------|
| <b>Length</b>            | 53 mm   2.087 in |
| <b>Diameter, maximum</b> | 35 mm   1.378 in |

## Electrical Specifications

|                                 |              |
|---------------------------------|--------------|
| <b>Average Power, maximum</b>   | 10 W         |
| <b>Impedance</b>                | 50 ohm       |
| <b>Operating Frequency Band</b> | 0 – 6000 MHz |
| <b>VSWR</b>                     | 1.15         |

## Environmental Specifications

|                                       |                                      |
|---------------------------------------|--------------------------------------|
| <b>Operating Temperature</b>          | -35 °C to +50 °C (-31 °F to +122 °F) |
| <b>Relative Humidity</b>              | Up to 100%                           |
| <b>Ingress Protection Test Method</b> | IEC 60529:2001, IP65                 |

## Packaging and Weights

# T-10-UW-43-M

---

|                       |                    |
|-----------------------|--------------------|
| <b>Height, packed</b> | 53 mm   2.087 in   |
| <b>Width, packed</b>  | 58 mm   2.283 in   |
| <b>Length, packed</b> | 68 mm   2.677 in   |
| <b>Weight, gross</b>  | 0.16 kg   0.353 lb |
| <b>Weight, net</b>    | 0.13 kg   0.287 lb |

## Regulatory Compliance/Certifications

### Agency

CHINA-ROHS

ISO 9001:2015

REACH-SVHC

ROHS

UK-ROHS

### Classification

Below maximum concentration value

Designed, manufactured and/or distributed under this quality management system

Compliant as per SVHC revision on [www.andrew.com/ProductCompliance](http://www.andrew.com/ProductCompliance)

Compliant

Compliant

