



TCS2® Heat-Shrink Cable Seal, 48 inch long, 0.75 inch recovered ID, 0.08 inch recovered wall thickness

- Used for insulating and sealing underground and aerial connections in CATV plant
- Also used in low voltage (600V) electrical power distribution applications
- Thermo-chromic stripes signifying adhesive flow and sleeve recovery
- Ensures an environmental seal and protection against moisture and water penetration

## Product Classification

<b>Regional Availability</b>	North America
<b>Product Type</b>	Heat shrink tubing, medium wall
<b>Product Brand</b>	TCS2®
<b>Product Series</b>	TCS2

## General Specifications

<b>Color</b>	Black
<b>Sealant Type</b>	Precoated water-insoluble

## Dimensions

<b>Length</b>	1,219.2 mm   48 in
<b>Expanded Inside Diameter, minimum</b>	50.8 mm   2 in
<b>Recovered Inside Diameter, maximum</b>	19 mm   0.748 in
<b>Recovered Wall Thickness, nominal</b>	2.03 mm   0.08 in

## Material Specifications

<b>Material Type</b>	Polyolefin
----------------------	------------

## Environmental Specifications

<b>Environmental Space</b>	Aerial
<b>Qualification Standards</b>	Telcordia GR-449-CORE, Issue 2

## Packaging and Weights

<b>Packaging quantity</b>	1
---------------------------	---

**Packaging Type**

Bag | Carton

### Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant
UK-ROHS	Compliant

