



## Fiber Breakout Kit, outside plant cable

**OBSOLETE**

### Product Classification

<b>Regional Availability</b>	Asia   Australia/New Zealand   EMEA   Latin America   North America
<b>Portfolio</b>	SYSTIMAX®
<b>Product Type</b>	Fiber breakout kit, rectangular
<b>Ordering Note</b>	Order B sealant separately

### General Specifications

<b>Application</b>	Buffers approximately 100 fibers
<b>Color</b>	Black
<b>Compatible Interface</b>	LC   LC, keyed   SC   ST

### Dimensions

<b>Tube Inner Diameter</b>	500 µm
<b>Tube Outer Diameter</b>	900 µm

### Material Specifications

<b>Material Type, body</b>	Acrylonitrile butadiene styrene (ABS)
<b>Material Type, tubing</b>	PVC

### Environmental Specifications

<b>Operating Temperature</b>	-10 °C to +60 °C (+14 °F to +140 °F)
------------------------------	--------------------------------------

### Packaging and Weights

<b>Included</b>	Buffer tubing, 900 micron, 210 ft   Clear PVC tubing, 1 ft, 0.234 in ID   Clear PVC tubing, 2 ft, 0.166 in ID   Clear PVC tubing, 25 ft, 0.095 in ID   Eight unit splitter with clear cover   Five syringes with applicator tip   Heat shrink tubing, 2 ft, 0.187 in ID   Instruction sheet   Rosin bag   Six clear PVC
-----------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

tubes, 2 in, 0.294 in ID | Six unit splitter with clear cover | Wire marker book

**Packaging quantity** 1

### Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant
UK-ROHS	Compliant

