

SP-10400L1L1CBAA | PLC 1X4 900UM IN/OUT LC /UPC GRADE C



Wideband PLC Splitter, singlemode, 1x4, symmetrical split ratio, 0.900 mm cable, LC/UPC grade C

Product Classification

Regional Availability

Asia | Australia/New Zealand | China | EMEA | India | Latin America | North America

Product Type

Bare splitter

General Specifications

Device Type

Component, rectangular

Functionality

Splitting

Technology Type

Planar lightwave circuit (PLC)

Distribution Type

1 x 4 splitter

Interface, Input

LC

Interface, Output

LC

Interface Feature, Output

UPC

Split Ratio

Symmetrical

Splitter, quantity

1

Dimensions

Height

4 mm | 0.157 in

Width

7 mm | 0.276 in

Length

60 mm | 2.362 in

Pigtail Length, Input

1 m | 3.281 ft

Pigtail Length, Output

1 m | 3.281 ft

Pigtail Diameter, Input

0.9 mm | 0.035 in

Pigtail Diameter, Output

0.9 mm | 0.035 in

Optical Specifications

Fiber Type

G.657.A2

SP-10400L1L1CBAA | PLC 1X4 900UM IN/OUT LC /UPC GRADE C

Directivity, minimum	55 dB
Polarization Dependent Loss, maximum	0.2 dB
Uniformity, maximum	1 dB
Wavelength Range	1260–1650 nm
Insertion Loss, Splitter, maximum	7.7 dB
Return Loss, Splitter, minimum	50 dB

Environmental Specifications

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Relative Humidity	5%–95%, non-condensing

Packaging and Weights

Packaging quantity	1
---------------------------	---