1-2055083-0 | OCJ-S1-10MASHA-S2



Fiber Optic Patch Cord, Duplex, Singlemode, SC/UPC to SC/APC, yellow, 10 m

Product Classification

Regional Availability	EMEA
Product Type	Fiber patch cord, duplex
Product Series	OCJ
General Specifications	
Connector A, quantity	2
Color, boot A	Blue
Color, connector A	Blue
Connector B, quantity	2
Color, boot B	Green
Color, connector B	Green
Interface, Connector A	SC/UPC
Interface, Connector B	SC/APC
Jacket Color	Yellow
Total Fibers, quantity	2
Dimensions	
Cable Assembly Length Range (m)	1 – 999
Cable Assembly Length Range (ft)	1 – 999
Cord Length	10 m 32.808 ft
Diameter Over Jacket	1.8 mm 0.071 in

Ordering Tree

Page 1 of 3

©2023 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: October 16, 2023



1-2055083-0 | OCJ-S1-10MASHA-S2

$OCJ - \underline{X} \underline{X} - \underline{X} \underline{X} \underline{M} \underline{X} \underline{X} \underline{X} \underline{X} - \underline{X} \underline{X}$

Connector type at end 1		
Standard C grade	Superior B grade	Туре
S1	SF	SC/UPC
S2	SG	SC/APC 8°
S3	SH	SC/APC 9°
L1	LF	LC/UPC
L2	LG	LC/APC
-	EC	LSH/APC 8°

Connector	type at end	2 1
-----------	-------------	------------

Standard C grade	Superior B grade	Туре
S1	SF	SC/UPC
S2	SG	SC/APC 8°
S3		SC/APC 9°
L1	LF	LC/UPC
L2	LG	LC/APC
	EC	LSH/APC 8°

¹ For hybrid patch cords, connectors 1 and 2 must be the same grade.

Cable length		
01	1 meter	
02	2 meters	
	3 meters	
	5 meters	
	10 meters	
	15 meters	
20	20 meters	
25	25 meters	
30	30 meters	

Cable type		
 ASIA	1.8mm simplex	LSZH jacket
ASHA	1.8mm duplex	LSZH jacket

Optical Specifications

Fiber Mode	Singlemode
Fiber Type	G.657.A1, TeraSPEED®
Performance Grade	Standard C grade
Insertion Loss, maximum, connector A	0.5 dB
Insertion Loss, maximum, connector B	0.5 dB
Return Loss, minimum, connector A	50 dB
Return Loss, minimum, connector B	60 dB

Environmental Specifications

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Environmental Space	Low Smoke Zero Halogen (LSZH)
Dackaging and Moights	

Packaging and Weights

Packaging quantity

Page 2 of 3

©2023 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: October 16, 2023

1



1-2055083-0 | OCJ-S1-10MASHA-S2

Regulatory Compliance/Certifications

Agency

ROHS

Classification

CHINA-ROHS Above maximum concentration value

Compliant/Exempted

Compliant/Exempted



UK-ROHS

* Footnotes

Performance Grade Guarantee to meet IEC 61755-1 Random Mating requirement

Page 3 of 3

©2023 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: October 16, 2023

